

| | | | |
|--------------------|---|-----------------|---|
| Project | Hywind-class FPSO — topside process module M-42 | Area | M-42 / EL bulk |
| Client | Havlinjen Energi AS | Enquiry | RFQ-2026-0411 (cable support & containment) |
| Environment | Offshore, splash-zone exposed — 316L preferred unless noted | Standard | IEC 61537, NORSOK M-501 coatings |

Cable management & support — bill of materials

| ITEM | DESCRIPTION | MATERIAL / FINISH | QTY | UNIT |
|------|--|--------------------|------|------|
| 1 | Cable ladder, 600 mm wide, 6 m length | 316L stainless | 80 | pcs |
| 2 | Cable ladder, 300 mm wide, 6 m length | 316L stainless | 120 | pcs |
| 3 | Cable ladder, 450 mm wide, 6 m length | Hot-dip galvanised | 60 | pcs |
| 4 | Flat elbow 90°, for 300 mm cable ladder | 316L stainless | 40 | pcs |
| 5 | Cable tray, return-flange, 200 mm, 3 m | 316L stainless | 240 | pcs |
| 6 | Cable tray, 100 mm, 3 m | Hot-dip galvanised | 180 | pcs |
| 7 | Support channel, Mekano CH50, 3 m | 316L stainless | 150 | pcs |
| 8 | Strut channel, Unistrut P1000, 41×41, 3 m | Stainless steel | 200 | pcs |
| 9 | Tube clamp, ETIN-S, 20 mm O.D. | Stainless steel | 600 | pcs |
| 10 | Tube clamp, Stauff DIN 3015 series 2, 22 mm O.D. | 316L stainless | 300 | pcs |
| 11 | Cable cleat, SmartCleit trefoil, 40 mm cable | 316L stainless | 500 | pcs |
| 12 | Hexagon bolt M10×20 with flange nut | A4 stainless | 2000 | pcs |

Notes. (1) Substitution permitted with technically-equivalent product subject to client approval — state proposed make/part and load class. (2) All ladder/tray to be supplied with matching couplers and fixings. (3) Competitor references (Unistrut, Stauff) are for sizing only; equivalent offered product acceptable. (4) Prices to be quoted per unit, NOK, ex-works, with lead time.